

View Online at <https://aerobasegroup.com/nsn/5306-00-056-7950>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.716 inches and 0.766 inches

Fastener Length:

Between 3.226 inches and 3.256 inches

Head Style:

Double hexagon extended washer

Head Height:

Between 0.494 inches and 0.514 inches

Width Between Flats:

Between 0.556 inches and 0.565 inches

Extended Washer Diameter:

Between 0.818 inches and 0.828 inches

Extended Washer Thickness:

Between 0.113 inches and 0.133 inches

Grip Diameter:

Between 0.4985 inches and 0.4995 inches

Thread Diameter:

0.500 inches

Grip Length:

Between 0.249 inches and 0.251 inches

Thready Qty Per Inch (tpi):

20

Min. Tensile Strength (psi):

180000 pounds per square inch

Hardness Rating:

39.0 rockwell c and 43.0 rockwell c

Surface Finish:

32.0 microinches grip

Material:

Steel comp e4340 or steel comp 4140 or steel comp 8740 or steel comp 8735

Surface Treatment:

Cadmium

Surface Treatment Specification:

Qq-p-416, type 2 federal specification single treatment response

Thread Series Designator:

Unjf

Specification Data:

80205-nas628 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0