

View Online at <https://aerobasegroup.com/nsn/5306-00-057-2781>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

0.360 inches

**Fastener Length:**

3.105 inches

**Head Style:**

Hexagon

**Head Height:**

0.327 inches

**Width Between Flats:**

0.940 inches

**Hole Diameter:**

0.062 inches

**Shank Unthreaded Hole Diameter:**

0.110 inches first hole

**First Diameter From Head:**

0.623 inches

**Second Diameter From Head:**

0.443 inches

**Third Diameter From Head:**

0.623 inches

**Fourth Diameter From Head:**

0.427 inches

**Distance From Largest Bearing Surface Of Head To End Of First Diameter:**

0.745 inches

**Distance From Largest Bearing Surface Of Head To End Of Second Diameter:**

2.020 inches

**Distance From Largest Bearing Surface Of Head To End Of Third Diameter:**

2.640 inches

**Distance From Largest Bearing Surface Of Head To End Of Fourth Diameter:**

2.745 inches

**Thread Diameter:**

0.500 inches

**Hole Quantity:**

1

**Hole Type:**

Drilled

**Thready Qty Per Inch (tpi):**

20

**Hole Configuration Style:**

Hexagon flats

**Distance From Head Largest Bearing Surface To Shank Hole Center:**

2.919 inches first hole

**Externally Relieved Body Diameter Quantity:**

4

**Material:**

Steel

**Surface Treatment:**

Nickel and cadmium

**Thread Series Designator:**

Unf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0