## NSN 5306-00-057-7786

Machine Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-00-057-7786

| Thread Class:                                     |
|---|
| 1a  |
| Thread Direction:                                 |
| Right-hand  |
| Thread Length:                                    |
| Between 0.935 inches and 0.975 inches             |
| Fastener Length:                                  |
| 1.062 inches                                      |
| Head Style:                                       |
| Double hexagon w/hole                             |
| Head Height:                                      |
| 0.375 inches                                      |
| Width Between Flats:                              |
| Between 0.367 inches and 0.376 inches             |
| Extended Washer Diameter:                         |
| 0.500 inches                                      |
| Extended Washer Thickness:                        |
| Between 0.070 inches and 0.080 inches             |
| Hole Diameter:                                    |
| 0.070 inches                                      |
| Thread Diameter:                                  |
| 0.312 inches                                      |
| Grip Length:                                      |
| Between 0.128 inches and 0.188 inches             |
| Hole Quantity:                                    |
| 4   |
| Hole Type:  |
| Drilled   |
| Features Provided:                                |
| Finished head                                     |
| Thready Qty Per Inch (tpi):                       |
| 24  |
| Min. Tensile Strength (psi):                      |
| 130000 pounds per square inch                     |
| Hardness Rating:                                  |
| 248.0 brinell standard and 341.0 brinell standard |
| Minimum Yield Strength:                           |
| 85000 pounds per square inch                      |
| Hole Configuration Style:                         |
| Double hexagon longitudinal hole                  |
| Surface Finish:                                   |
| 63.0 microinches grip                             |
|   |

## NSN 5306-00-057-7786

Machine Bolt - Page 2 of 2



| Material:                                       |
|---|
| Iron alloy 660                                  |
| Material Specification:                         |
| Ams 5737 assn standard single material response |
| Thread Series Designator:                       |
| Unf   |
| Shelf Life:                                     |
| N/a   |
| Unit Of Measure:                                |
|   |
| Demilitarization:                               |
| No  |

Fiig: A003b0