## NSN 5306-00-058-1424

Internally Relieved Body Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-00-058-1424 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.730 inches **Fastener Length:** 5.650 inches **Head Style:** Hexagon **Head Height:** 0.190 inches Width Between Flats: 1.062 inches **Shank Unthreaded Hole Diameter:** 0.140 inches first hole **Concentric Hole Diameter:** 0.500 inches **Thread Diameter:** 0.750 inches Thready Qty Per Inch (tpi): 16 Min. Tensile Strength (psi): 180000 pounds per square inch Hardness Rating: 39.0 rockwell c and 42.0 rockwell c Distance From Head Largest Bearing Surface To Shank Hole Center: 5.460 inches first hole Material: Steel comp 8740 **Material Specification:** Mil-s-6049 military specification single material response **Surface Treatment:** Cadmium **Style Designator:** Concentric hole unthreaded **Thread Series Designator:** Unf Shelf Life: N/a

--

**Unit Of Measure:** 

## NSN 5306-00-058-1424

Internally Relieved Body Bolt - Page 2 of 2



| em |  |  |  |
|----|--|--|--|
|    |  |  |  |

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-6049 spec.