## NSN 5306-00-058-2146

Close Tolerance Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-00-058-2146 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.444 inches and 0.494 inches **Fastener Length:** Between 2.266 inches and 2.296 inches **Head Style:** Hexagon **Head Height:** Between 0.156 inches and 0.171 inches Width Between Flats: Between 0.492 inches and 0.502 inches **Grip Diameter:** Between 0.3115 inches and 0.3120 inches **Shank Unthreaded Hole Diameter:** 0.076 inches first hole and 0.086 inches first hole **Thread Diameter:** 0.312 inches **Grip Length:** Between 1.802 inches and 1.822 inches Thready Qty Per Inch (tpi): 24 Distance From Head Largest Bearing Surface To Shank Hole Center: 2.075 inches first hole and 2.125 inches first hole **Surface Finish:** 63.0 microinches grip Material: Titanium alloy **Material Specification:** Ams 4928 assn standard single material response or nas 621 6al-4v assn standard single material response **Thread Series Designator:** Unjf **Specification Data:** 80205-nas675 professional/industrial association standard Shelf Life: N/a **Unit Of Measure:** 

Demilitarization:

No

## **NSN 5306-00-058-2146**Close Tolerance Bolt - Page 2 of 2



Fiig:

A003b0