NSN 5306-00-058-6687

Externally Relieved Body Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-00-058-6687 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.628 inches and 0.688 inches **Fastener Length:** 1.250 inches **Head Style:** Double hexagon w/hole **Head Height:** 0.330 inches Width Between Flats: Between 0.304 inches and 0.313 inches **Extended Washer Diameter:** 0.438 inches **Extended Washer Thickness:** Between 0.060 inches and 0.070 inches **Hole Diameter:** 0.070 inches First Diameter From Head: Between 0.221 inches and 0.231 inches **Second Diameter From Head:** Between 0.246 inches and 0.249 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.060 inches and 0.070 inches Distance From Largest Bearing Surface Of Head To End Of Second Diameter: Between 0.502 inches and 0.562 inches **Thread Diameter:** 0.250 inches **Hole Quantity: Hole Type:** Drilled Thready Qty Per Inch (tpi): **Hole Configuration Style:** Round **Externally Relieved Body Diameter Quantity:**

2

Material:

Steel comp 630

NSN 5306-00-058-6687

Externally Relieved Body Bolt - Page 2 of 2



Material Specification:
Ams 5643 assn standard single material response
Thread Series Designator:
Unjf
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:

No

Fiig:

A003b0