

View Online at <https://aerobasegroup.com/nsn/5306-00-058-9259>

Thread Class:

2a

Thread Direction:

Right-hand

Thread Length:

0.525 inches

Fastener Length:

Between 5.900 inches and 6.060 inches

Head Style:

Button

Head Diameter:

Between 0.563 inches and 0.594 inches

Head Height:

Between 0.125 inches and 0.145 inches

Neck Length:

Between 0.125 inches and 0.156 inches

Thread Diameter:

0.250 inches

Thready Qty Per Inch (tpi):

20

Min. Tensile Strength (psi):

60000 pounds per square inch

Hardness Rating:

95.0 rockwell b

Criticality Code Justification:

Sftt

Neck Width:

Between 0.245 inches and 0.260 inches

Material:

Steel comp 301 or steel comp 302 or steel comp 302b or steel comp 303 or steel comp 303se or steel comp 304 or steel comp 304l or steel comp 305 or steel comp 308 or steel comp 309 or steel comp 309s or steel comp 310 or steel comp 310s or steel comp 314 or steel comp 316 or steel comp 316l or steel comp 317 or steel comp 321 or steel comp 347 or steel comp 348 or steel comp 384 or steel comp 385

Surface Treatment:

Zinc and chromate

Surface Treatment Specification:

Qq-z-325, type 2 class 3 federal specification single treatment response or mil-c-81562, type 2 class 3 military specification single treatment response

Thread Series Designator:

Unc

Specification Or Standard:

1 type and 1 class and a style

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-c-81562 spec.