

View Online at <https://aerobasegroup.com/nsn/5306-00-058-9259>

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Thread Length:**

0.525 inches

**Fastener Length:**

Between 5.900 inches and 6.060 inches

**Head Style:**

Button

**Head Diameter:**

Between 0.563 inches and 0.594 inches

**Head Height:**

Between 0.125 inches and 0.145 inches

**Neck Length:**

Between 0.125 inches and 0.156 inches

**Thread Diameter:**

0.250 inches

**Thready Qty Per Inch (tpi):**

20

**Min. Tensile Strength (psi):**

60000 pounds per square inch

**Hardness Rating:**

95.0 rockwell b

**Criticality Code Justification:**

Sftt

**Neck Width:**

Between 0.245 inches and 0.260 inches

**Material:**

Steel comp 301 or steel comp 302 or steel comp 302b or steel comp 303 or steel comp 303se or steel comp 304 or steel comp 304l or steel comp 305 or steel comp 308 or steel comp 309 or steel comp 309s or steel comp 310 or steel comp 310s or steel comp 314 or steel comp 316 or steel comp 316l or steel comp 317 or steel comp 321 or steel comp 347 or steel comp 348 or steel comp 384 or steel comp 385

**Surface Treatment:**

Zinc and chromate

**Surface Treatment Specification:**

Qq-z-325, type 2 class 3 federal specification single treatment response or mil-c-81562, type 2 class 3 military specification single treatment response

**Thread Series Designator:**

Unc

**Specification Or Standard:**

1 type and 1 class and a style

**Shelf Life:**

N/a

**Unit Of Measure:**

**Demilitarization:**

No

**Fiig:**

A003b0

**Mil-std (military Standard):**

Mil-c-81562 spec.