

View Online at <https://aerobasegroup.com/nsn/5306-00-059-2602>

Thread Class:

2a

Thread Direction:

Right-hand

Thread Length:

Between 0.679 inches and 0.741 inches

Fastener Length:

Between 0.750 inches and 0.812 inches

Head Style:

Hexagon

Head Height:

Between 0.120 inches and 0.140 inches

Width Between Flats:

Between 0.615 inches and 0.627 inches

Thread Diameter:

0.250 inches

Features Provided:

Finished head

Thready Qty Per Inch (tpi):

28

Min. Tensile Strength (psi):

125000 pounds per square inch

Material:

Steel comp 4130 or steel comp 4140 or steel comp 4037 or steel comp 8630 or steel comp 8735 or steel comp 8740

Material Specification:

Mil-s-6758 military specification 1st material response or mil-s-5626 military specification 2nd material response or mil-s-8695 military specification 3rd material response or mil-s-6050 military specification 4th material response or mil-s-6098 military specification 5th material response or mil-s-6049 military specification 6th material response

Surface Treatment:

Cadmium and zinc

Surface Treatment Specification:

Qq-p-416ty1cl2 federal specification 1st treatment response and qq-z-325 federal specification 2nd treatment response

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A003b0

Mil-std (military Standard):

Mil-s-6758 spec.