

View Online at <https://aerobasegroup.com/nsn/5306-00-060-9350>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

0.430 inches

**Fastener Length:**

1.620 inches

**Head Style:**

Hexagon

**Head Height:**

0.200 inches

**Width Between Flats:**

Between 0.740 inches and 0.752 inches

**Shoulder Diameter:**

0.500 inches first shoulder

**Shoulder Length:**

1.190 inches first shoulder

**Shank Unthreaded Hole Diameter:**

0.106 inches first hole

**Thread Diameter:**

0.438 inches

**Thready Qty Per Inch (tpi):**

20

**Min. Tensile Strength (psi):**

180000 pounds per square inch

**Hardness Rating:**

39.0 rockwell c and 43.0 rockwell c

**Distance From Head Largest Bearing Surface To Shank Hole Center:**

1.490 inches first hole

**Shoulder Shape:**

Round first shoulder

**Material:**

Steel comp 4130

**Material Specification:**

Mil-s-6758, f4 military specification single material response

**Surface Treatment:**

Cadmium

**Thread Series Designator:**

Unf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0

**Mil-std (military Standard):**

Mil-s-6758 spec.