## NSN 5306-00-061-3008

Machine Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-00-061-3008

Thread Direction: Right-hand Thread Length: 0.906 inches Fastener Length: 1.719 inches Head Style: Double hexagon w/hole Head Height: 0.530 inches Width Between Flats: Between 0.616 inches and 0.627 inches Extended Washer Diameter: Between 0.940 inches and 0.950 inches Extended Washer Thickness: 0.098 inches Thread Diameter: 0.500 inches Grip Length: 0.813 inches Features Provided: Finished head Thready Qty Per Inch (tpi): 20 Min. Tensile Strength (psi): 220000 pounds per square inch Hardness Rating:
Thread Direction: Right-hand Thread Length: 0.906 inches Fastener Length: 1.719 inches Head Style: Double hexagon w/hole Head Height: 0.530 inches Width Between Flats: Between 0.616 inches and 0.627 inches Extended Washer Diameter: Between 0.940 inches and 0.950 inches Extended Washer Thickness: 0.098 inches Thread Diameter: 0.500 inches Grip Length: 0.813 inches Features Provided: Finished head Thready Qty Per Inch (tpi): 20 Min. Tensile Strength (psi): 220000 pounds per square inch Hardness Rating:
Right-hand Thread Length: 0.906 inches Fastener Length: 1.719 inches Head Style: Double hexagon w/hole Head Height: 0.530 inches Width Between Flats: Between 0.616 inches and 0.627 inches Extended Washer Diameter: Between 0.940 inches and 0.950 inches Extended Washer Thickness: 0.098 inches Thread Diameter: 0.500 inches Grip Length: 0.813 inches Features Provided: Finished head Thready Qty Per Inch (tpi): 20 Min. Tensile Strength (psi): 220000 pounds per square inch Hardness Rating:
Thread Length: 0.906 inches Fastener Length: 1.719 inches Head Style: Double hexagon w/hole Head Height: 0.530 inches Width Between Flats: Between 0.616 inches and 0.627 inches Extended Washer Diameter: Between 0.940 inches and 0.950 inches Extended Washer Thickness: 0.098 inches Thread Diameter: 0.500 inches Grip Length: 0.813 inches Features Provided: Finished head Thready Qty Per Inch (tpi): 20 Min. Tensile Strength (psi): 220000 pounds per square inch Hardness Rating:
0.906 inches Fastener Length: 1.719 inches Head Style: Double hexagon w/hole Head Height: 0.530 inches Width Between Flats: Between 0.616 inches and 0.627 inches Extended Washer Diameter: Between 0.940 inches and 0.950 inches Extended Washer Thickness: 0.098 inches Thread Diameter: 0.500 inches Grip Length: 0.813 inches Features Provided: Finished head Thready Qty Per Inch (tpi): 20 Min. Tensile Strength (psi): 220000 pounds per square inch Hardness Rating:
Fastener Length:  1.719 inches  Head Style:  Double hexagon w/hole  Head Height:  0.530 inches  Width Between Flats:  Between 0.616 inches and 0.627 inches  Extended Washer Diameter:  Between 0.940 inches and 0.950 inches  Extended Washer Thickness:  0.098 inches  Thread Diameter:  0.500 inches  Grip Length:  0.813 inches  Features Provided:  Finished head  Thready Qty Per Inch (tpi):  20  Min. Tensile Strength (psi):  220000 pounds per square inch  Hardness Rating:
1.719 inches  Head Style:  Double hexagon w/hole  Head Height: 0.530 inches  Width Between Flats:  Between 0.616 inches and 0.627 inches  Extended Washer Diameter:  Between 0.940 inches and 0.950 inches  Extended Washer Thickness: 0.098 inches  Thread Diameter: 0.500 inches  Grip Length: 0.813 inches  Features Provided: Finished head  Thready Qty Per Inch (tpi): 20  Min. Tensile Strength (psi): 220000 pounds per square inch  Hardness Rating:
Head Style: Double hexagon w/hole Head Height: 0.530 inches Width Between Flats: Between 0.616 inches and 0.627 inches Extended Washer Diameter: Between 0.940 inches and 0.950 inches Extended Washer Thickness: 0.098 inches Thread Diameter: 0.500 inches Grip Length: 0.813 inches Features Provided: Finished head Thready Qty Per Inch (tpi): 20 Min. Tensile Strength (psi): 220000 pounds per square inch Hardness Rating:
Double hexagon w/hole  Head Height: 0.530 inches  Width Between Flats: Between 0.616 inches and 0.627 inches  Extended Washer Diameter: Between 0.940 inches and 0.950 inches  Extended Washer Thickness: 0.098 inches  Thread Diameter: 0.500 inches  Grip Length: 0.813 inches  Features Provided: Finished head  Thready Qty Per Inch (tpi): 20  Min. Tensile Strength (psi): 220000 pounds per square inch  Hardness Rating:
Head Height:  0.530 inches  Width Between Flats: Between 0.616 inches and 0.627 inches  Extended Washer Diameter: Between 0.940 inches and 0.950 inches  Extended Washer Thickness:  0.098 inches  Thread Diameter:  0.500 inches  Grip Length:  0.813 inches  Features Provided: Finished head  Thready Qty Per Inch (tpi):  20  Min. Tensile Strength (psi):  220000 pounds per square inch  Hardness Rating:
Width Between Flats: Between 0.616 inches and 0.627 inches Extended Washer Diameter: Between 0.940 inches and 0.950 inches Extended Washer Thickness: 0.098 inches Thread Diameter: 0.500 inches Grip Length: 0.813 inches Features Provided: Finished head Thready Qty Per Inch (tpi): 20 Min. Tensile Strength (psi): 220000 pounds per square inch Hardness Rating:
Width Between Flats: Between 0.616 inches and 0.627 inches  Extended Washer Diameter: Between 0.940 inches and 0.950 inches  Extended Washer Thickness: 0.098 inches Thread Diameter: 0.500 inches Grip Length: 0.813 inches Features Provided: Finished head Thready Qty Per Inch (tpi): 20 Min. Tensile Strength (psi): 220000 pounds per square inch Hardness Rating:
Between 0.616 inches and 0.627 inches  Extended Washer Diameter:  Between 0.940 inches and 0.950 inches  Extended Washer Thickness:  0.098 inches  Thread Diameter:  0.500 inches  Grip Length:  0.813 inches  Features Provided:  Finished head  Thready Qty Per Inch (tpi):  20  Min. Tensile Strength (psi):  220000 pounds per square inch  Hardness Rating:
Extended Washer Diameter:  Between 0.940 inches and 0.950 inches  Extended Washer Thickness:  0.098 inches  Thread Diameter:  0.500 inches  Grip Length:  0.813 inches  Features Provided: Finished head  Thready Qty Per Inch (tpi):  20  Min. Tensile Strength (psi):  220000 pounds per square inch  Hardness Rating:
Between 0.940 inches and 0.950 inches  Extended Washer Thickness:  0.098 inches  Thread Diameter:  0.500 inches  Grip Length:  0.813 inches  Features Provided: Finished head  Thready Qty Per Inch (tpi):  20  Min. Tensile Strength (psi):  220000 pounds per square inch  Hardness Rating:
Extended Washer Thickness:  0.098 inches  Thread Diameter:  0.500 inches  Grip Length:  0.813 inches  Features Provided:  Finished head  Thready Qty Per Inch (tpi):  20  Min. Tensile Strength (psi):  220000 pounds per square inch  Hardness Rating:
0.098 inches Thread Diameter: 0.500 inches Grip Length: 0.813 inches Features Provided: Finished head Thready Qty Per Inch (tpi): 20 Min. Tensile Strength (psi): 220000 pounds per square inch Hardness Rating:
Thread Diameter:  0.500 inches  Grip Length:  0.813 inches  Features Provided: Finished head  Thready Qty Per Inch (tpi): 20  Min. Tensile Strength (psi): 220000 pounds per square inch  Hardness Rating:
Grip Length:  0.813 inches  Features Provided: Finished head  Thready Qty Per Inch (tpi): 20  Min. Tensile Strength (psi): 220000 pounds per square inch  Hardness Rating:
Grip Length:  0.813 inches  Features Provided: Finished head  Thready Qty Per Inch (tpi): 20  Min. Tensile Strength (psi): 220000 pounds per square inch  Hardness Rating:
0.813 inches  Features Provided: Finished head  Thready Qty Per Inch (tpi): 20  Min. Tensile Strength (psi): 220000 pounds per square inch  Hardness Rating:
Features Provided: Finished head Thready Qty Per Inch (tpi): 20 Min. Tensile Strength (psi): 220000 pounds per square inch Hardness Rating:
Finished head  Thready Qty Per Inch (tpi): 20  Min. Tensile Strength (psi): 220000 pounds per square inch  Hardness Rating:
Thready Qty Per Inch (tpi): 20 Min. Tensile Strength (psi): 220000 pounds per square inch Hardness Rating:
20 Min. Tensile Strength (psi): 220000 pounds per square inch Hardness Rating:
220000 pounds per square inch Hardness Rating:
220000 pounds per square inch Hardness Rating:
Hardness Rating:
46.0 rockwell c and 49.0 rockwell c
Material:
Steel
Material Specification:
Sps-m-107, standard pressed steel co mfr ref single material response
Surface Treatment:
Cadmium
Thread Series Designator:
Unf
Shelf Life:
N/a
Unit Of Measure:

## NSN 5306-00-061-3008

Machine Bolt - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0