

View Online at <https://aerobasegroup.com/nsn/5306-00-061-7948>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

0.470 inches

**Fastener Length:**

2.320 inches

**Head Style:**

Hexagon

**Head Height:**

0.240 inches

**Width Between Flats:**

1.438 inches

**Shoulder Diameter:**

1.122 inches first shoulder and 1.123 inches first shoulder

**Shoulder Length:**

1.850 inches first shoulder

**Shank Unthreaded Hole Diameter:**

0.109 inches first hole

**Thread Diameter:**

0.375 inches

**Thready Qty Per Inch (tpi):**

24

**Min. Tensile Strength (psi):**

180000 pounds per square inch

**Hardness Rating:**

39.0 rockwell c and 43.0 rockwell c

**Distance From Head Largest Bearing Surface To Shank Hole Center:**

2.140 inches first hole

**Shoulder Shape:**

Round first shoulder

**Material:**

Steel comp 4140

**Material Specification:**

Mil-s-5626 comp 4140 military specification single material response

**Thread Series Designator:**

Unf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A003b0

**Mil-std (military Standard):**

Mil-s-5626 spec.