

View Online at <https://aerobasegroup.com/nsn/5306-00-062-0818>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

0.544 inches

Fastener Length:

0.699 inches

Head Style:

Hexagon

Head Height:

0.156 inches

Width Between Flats:

Between 0.430 inches and 0.439 inches

Hole Diameter:

0.046 inches

Shank Unthreaded Hole Diameter:

0.076 inches first hole

Thread Diameter:

0.250 inches

Grip Length:

0.125 inches

Hole Quantity:

1

Hole Type:

Drilled

Features Provided:

Finished head

Thready Qty Per Inch (tpi):

28

Min. Tensile Strength (psi):

140000 pounds per square inch

Hole Configuration Style:

Hexagon flats

Distance From Head Largest Bearing Surface To Shank Hole Center:

0.437 inches first hole

Material:

Iron alloy 660

Material Specification:

Ams5732 assn standard 1st material response or ams5737 assn standard 1st material response or ams5733 assn standard 2nd material response

Surface Treatment:

Passivate

Surface Treatment Specification:

Mil-s-5002 military specification single treatment response

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-5002 spec.