NSN 5306-00-062-0822



Machine Bolt - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5306-00-062-0822 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.544 inches **Fastener Length:** 1.044 inches **Head Style:** Hexagon **Head Height:** 0.156 inches Width Between Flats: Between 0.430 inches and 0.439 inches **Hole Diameter:** 0.062 inches **End Application:** W/s: 485l tacs; aircraft, orion p-3; aircraft, thunderbolt ii, a-10; deep submergence systems programs (dssp); tactical air opns module (an/tyq (23); aircraft, t-37; aircraft, t-38; aircraft, freedom fighter f-5; aircraft, starlifter c-141; aircraft, galaxy c-5 **Thread Diameter:** 0.250 inches **Grip Length:** Between 0.485 inches and 0.515 inches **Hole Quantity:** 1 **Hole Type:** Drilled **Features Provided:** Finished head Thready Qty Per Inch (tpi): 28 Minimum Yield Strength: 85000 pounds per square inch **Hole Configuration Style:** Hexagon flats

Material:

Stainless steel

Surface Treatment:

Passivate

Thread Series Designator:

Unf

Specification Data:

80205-nas1004 professional/industrial association standard

NSN 5306-00-062-0822

Machine Bolt - Page 2 of 2



_			-		
C	hο	14		.ife	
•			_	.II C	-

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0