

View Online at <https://aerobasegroup.com/nsn/5306-00-063-3754>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

0.544 inches

**Fastener Length:**

1.232 inches

**Head Style:**

Hexagon

**Head Height:**

0.156 inches

**Width Between Flats:**

Between 0.430 inches and 0.439 inches

**Shank Unthreaded Hole Diameter:**

0.076 inches first hole

**Thread Diameter:**

0.250 inches

**Grip Length:**

0.688 inches

**Features Provided:**

Finished head

**Thready Qty Per Inch (tpi):**

28

**Distance From Head Largest Bearing Surface To Shank Hole Center:**

1.000 inches first hole

**Material:**

Iron alloy 660

**Material Specification:**

Ams 5732 assn standard 1st material response or ams 5737 assn standard 1st material response or ams 5733 assn standard 2nd material response

**Surface Treatment:**

Passivate

**Surface Treatment Specification:**

Mil-s-5002 military specification single treatment response

**Thread Series Designator:**

Unf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A003b0

**Mil-std (military Standard):**

Mil-s-5002 spec.