Externally Relieved Body Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-00-064-8419

view Online	at https://aerobasegroup.com/nsn/5306-00-064-8419
Thread Cla	ISS:
3a	
Thread Dire	ection:
Right-hand	
Thread Ler	ngth:
0.500 inche	S
Fastener Lo	ength:
1.250 inche	S
Head Style	:
Hexagon	
Head Heigh	ht:
0.250 inche	S
Width Betw	veen Flats:
0.500 inche	S
Hole Diame	eter:
0.062 inche	S
First Diame	eter From Head:
0.312 inche	S
Second Dia	ameter From Head:
Between 0.3	326 inches and 0.327 inches
Distance F	rom Largest Bearing Surface Of Head To End Of First Diameter:
0.031 inche	S
Distance F	rom Largest Bearing Surface Of Head To End Of Second Diameter
0.750 inche	S
Thread Dia	meter:
0.312 inche	S
Hole Quant	tity:
1	
Hole Type:	
Drilled	
Thready Qt	ty Per Inch (tpi):
24	
Hardness F	Rating:
25.0 rockwe	ell c and 28.0 rockwell c
Hole Config	guration Style:
Hexagon fla	ats
Externally	Relieved Body Diameter Quantity:
2	
Material:	
Steel comp	304
Surface Tre	eatment:
Phosphate	

NSN 5306-00-064-8419

Externally Relieved Body Bolt - Page 2 of 2



Surface Treatment Specification:

Mil-c-16232, type 2 military specification single treatment response

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-c-16232 spec.