

View Online at <https://aerobasegroup.com/nsn/5306-00-068-0449>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.395 inches and 0.431 inches

Fastener Length:

Between 3.541 inches and 3.587 inches

Head Style:

Hexagon

Head Height:

Between 0.156 inches and 0.171 inches

Width Between Flats:

0.500 inches

Shoulder Diameter:

0.3110 inches first shoulder and 0.3120 inches first shoulder

Shoulder Length:

3.156 inches first shoulder

Shank Unthreaded Hole Diameter:

0.076 inches first hole and 0.086 inches first hole

Thread Diameter:

0.250 inches

Thready Qty Per Inch (tpi):

28

Min. Tensile Strength (psi):

160000 pounds per square inch

Hardness Rating:

39.0 rockwell c and 40.0 rockwell c

Distance From Head Largest Bearing Surface To Shank Hole Center:

3.374 inches first hole

Shoulder Shape:

Round first shoulder

Material:

Steel comp e4340

Material Specification:

Mil-s-5000 military specification single material response

Surface Treatment:

Cadmium

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-5000 spec.