NSN 5306-00-069-5427

Square Neck Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-00-069-5427

hread Class:	
а	
hread Direction:	
light-hand	
hread Length:	
.250 inches	
astener Length:	
etween 5.938 inches and 6.062 inches	
lead Style:	
Button	
lead Diameter:	
etween 1.032 inches and 1.094 inches	
lead Height:	
etween 0.250 inches and 0.270 inches	
leck Length:	
etween 0.250 inches and 0.281 inches	
hread Diameter:	
.500 inches	
hready Qty Per Inch (tpi):	
3	
lin. Tensile Strength (psi):	
5000 pounds per square inch	
lardness Rating:	
5.0 rockwell b	
leck Width:	
etween 0.492 inches and 0.515 inches	
laterial:	
iteel	
laterial Specification:	
ae gr 1 assn standard single material response	
Surface Treatment:	
admium or zinc	
surface Treatment Specification:	
	ponse or qq-z-325, type 2, cl 3 federal specification 2nd treatment response
hread Series Designator:	
Inc	
shelf Life:	
l/a	
Init Of Measure:	
init Of Measure:	
Demilitarization:	
lo	

NSN 5306-00-069-5427 Square Neck Bolt - Page 2 of 2

Fiig: A003b0

