

View Online at <https://aerobasegroup.com/nsn/5306-00-071-6627>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 1.562 inches and 1.612 inches

Fastener Length:

Between 7.197 inches and 7.227 inches

Head Style:

Double hexagon w/hole

Head Height:

Between 1.041 inches and 1.061 inches

Width Between Flats:

Between 1.245 inches and 1.255 inches

Extended Washer Diameter:

Between 1.865 inches and 1.875 inches

Extended Washer Thickness:

Between 0.248 inches and 0.268 inches

Grip Diameter:

Between 1.1225 inches and 1.1240 inches

Thread Diameter:

1.125 inches

Grip Length:

Between 5.615 inches and 5.635 inches

Thready Qty Per Inch (tpi):

12

Min. Tensile Strength (psi):

180000 pounds per square inch

Hardness Rating:

39.0 rockwell c and 43.0 rockwell c

Material:

Steel comp e4340 or steel comp 4140 or steel comp 8740 or steel comp 8735

Material Specification:

Mil-s-5000 military specification 1st material response or mil-s-5626 military specification 2nd material response or mil-s-6049 military specification 3rd material response or mil-s-6098 military specification 4th material response

Surface Treatment:

Cadmium

Surface Treatment Specification:

Nas 672 assn standard single treatment response

Thread Series Designator:

Unf

Specification Data:

80205-nas638 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-5000 spec.