

View Online at <https://aerobasegroup.com/nsn/5306-00-071-8881>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.800 inches and 0.850 inches

**Fastener Length:**

Between 3.560 inches and 3.590 inches

**Head Style:**

Double hexagon w/hole

**Head Height:**

Between 0.547 inches and 0.567 inches

**Width Between Flats:**

Between 0.619 inches and 0.628 inches

**Extended Washer Diameter:**

Between 0.928 inches and 0.938 inches

**Extended Washer Thickness:**

Between 0.123 inches and 0.143 inches

**Grip Diameter:**

Between 0.5605 inches and 0.5615 inches

**Thread Diameter:**

0.562 inches

**Grip Length:**

Between 2.740 inches and 2.760 inches

**Thready Qty Per Inch (tpi):**

18

**Min. Tensile Strength (psi):**

180000 pounds per square inch

**Hardness Rating:**

39.0 rockwell c and 43.0 rockwell c

**Material:**

Steel comp 4140 or steel comp 8735 or steel comp 8740

**Surface Treatment:**

Cadmium

**Surface Treatment Specification:**

Nas 672 assn standard single treatment response

**Thread Series Designator:**

Unjf

**Specification Data:**

80205-nas629 professional/industrial association standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0