

View Online at <https://aerobasegroup.com/nsn/5306-00-071-8882>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 1.169 inches and 1.219 inches

Fastener Length:

Between 3.179 inches and 3.209 inches

Head Style:

Double hexagon w/hole

Head Height:

Between 0.798 inches and 0.818 inches

Width Between Flats:

Between 0.934 inches and 0.943 inches

Extended Washer Diameter:

Between 1.428 inches and 1.438 inches

Extended Washer Thickness:

Between 0.188 inches and 0.208 inches

Grip Diameter:

Between 0.8730 inches and 0.8740 inches

Thread Diameter:

0.875 inches

Grip Length:

Between 1.990 inches and 2.010 inches

Thready Qty Per Inch (tpi):

14

Min. Tensile Strength (psi):

180000 pounds per square inch

Hardness Rating:

39.0 rockwell c and 43.0 rockwell c

Material:

Steel comp 4140 or steel comp 8740 or steel comp 8735 or steel comp 6150

Surface Treatment:

Cadmium

Surface Treatment Specification:

Nas672 assn standard single treatment response

Thread Series Designator:

Unjf

Specification Data:

80205-nas634 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0