## NSN 5306-00-075-2768

Machine Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-00-075-2768 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.800 inches and 0.880 inches **Fastener Length:** Between 0.510 inches and 0.530 inches **Head Style:** Double hexagon extended washer **Head Height:** Between 0.410 inches and 0.430 inches Width Between Flats: Between 0.492 inches and 0.502 inches **Extended Washer Diameter:** 0.562 inches **Extended Washer Thickness:** Between 0.090 inches and 0.110 inches **Thread Diameter:** 0.312 inches **Grip Length:** Between 2.820 inches and 3.627 inches **Features Provided:** Finished head Thready Qty Per Inch (tpi): 24 Hardness Rating: 32.0 rockwell c and 38.0 rockwell c **Surface Finish:** 63.0 microinches bearing surface of head Material: Steel **Material Specification:** Ams 6322 assn standard single material response **Surface Treatment:** Cadmium **Surface Treatment Specification:** Ams 2400 assn standard single treatment response **Thread Series Designator:** Unf

Shelf Life: N/a

## **NSN 5306-00-075-2768** Machine Bolt - Page 2 of 2



			ıre:

Demilitarization:

No

Fiig:

A003b0