

View Online at <https://aerobasegroup.com/nsn/5306-00-075-5975>

Thread Class:

1a

Thread Direction:

Right-hand

Thread Length:

Between 0.900 inches and 0.920 inches

Fastener Length:

Between 0.900 inches and 0.920 inches

Head Style:

Double hexagon extended washer

Head Height:

Between 0.365 inches and 0.385 inches

Width Between Flats:

Between 0.367 inches and 0.376 inches

Extended Washer Diameter:

Between 0.490 inches and 0.510 inches

Extended Washer Thickness:

Between 0.070 inches and 0.080 inches

Hole Diameter:

0.070 inches

Shank Unthreaded Hole Diameter:

0.060 inches first hole and 0.080 inches first hole

Thread Diameter:

0.312 inches

Hole Quantity:

4

Hole Type:

Drilled

Features Provided:

Finished head

Thready Qty Per Inch (tpi):

24

Hardness Rating:

30.0 rockwell c and 38.0 rockwell c

Hole Configuration Style:

Square flats

Distance From Head Largest Bearing Surface To Shank Hole Center:

0.790 inches first hole and 0.810 inches first hole

Material:

Steel comp 601

Material Specification:

Ams 6304 assn standard single material response

Surface Treatment:

Nickel and cadmium

Surface Treatment Specification:

Ams 2416 assn standard all treatment responses

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0