

View Online at <https://aerobasegroup.com/nsn/5306-00-080-0132>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.715 inches and 0.795 inches

**Shank Length:**

Between 0.715 inches and 0.775 inches

**Eye Stock Diameter:**

0.688 inches

**Shoulder Diameter:**

Between 0.554 inches and 0.559 inches

**Shoulder Length:**

Between 1.990 inches and 2.010 inches

**Ring Stock Diameter:**

Between 0.375 inches and 0.395 inches

**Ring Inside Diameter:**

Between 0.178 inches and 0.198 inches

**Thread Diameter:**

0.437 inches

**Thready Qty Per Inch (tpi):**

20

**Min. Tensile Strength (psi):**

160000 pounds per square inch

**Hardness Rating:**

36.0 rockwell c and 40.0 rockwell c

**Special Features:**

Moveable ring

**Material:**

Steel comp e4340 or steel comp 4140 or steel comp 8740 or steel comp 8735 or steel comp 6150

**Surface Treatment:**

Cadmium and chromate or zinc

**Surface Treatment Specification:**

Qq-p-416 type 2 cl 2 federal specification 1st treatment response or astm-b-633 assn standard 2nd treatment response

**Style Designator:**

Swivel

**Thread Series Designator:**

Unjf

**Specification Data:**

80205-nas1251 professional/industrial association standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0