NSN 5306-00-080-9395

Machine Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-00-080-9395

Thread Class:

| Thread Direction: |
|---|
| Right-hand |
| Thread Length: |
| Between 0.283 inches and 0.303 inches |
| Fastener Length: |
| 0.375 inches |
| Head Style: |
| Hexagon |
| Head Height: |
| Between 0.134 inches and 0.150 inches |
| Width Between Flats: |
| Between 0.367 inches and 0.376 inches |
| Hole Diameter: |
| 0.062 inches |
| Thread Diameter: |
| 0.190 inches |
| Grip Length: |
| Between 0.072 inches and 0.092 inches |
| Hole Quantity: |
| 1 |
| Hole Type: |
| |
| Drilled |
| Features Provided: |
| |
| Features Provided: |
| Features Provided: Finished head |
| Features Provided: Finished head Thready Qty Per Inch (tpi): |
| Features Provided: Finished head Thready Qty Per Inch (tpi): 32 |
| Features Provided: Finished head Thready Qty Per Inch (tpi): 32 Minimum Yield Strength: |
| Features Provided: Finished head Thready Qty Per Inch (tpi): 32 Minimum Yield Strength: 85000 pounds per square inch |
| Features Provided: Finished head Thready Qty Per Inch (tpi): 32 Minimum Yield Strength: 85000 pounds per square inch Hole Configuration Style: |
| Features Provided: Finished head Thready Qty Per Inch (tpi): 32 Minimum Yield Strength: 85000 pounds per square inch Hole Configuration Style: Hexagon flats |
| Features Provided: Finished head Thready Qty Per Inch (tpi): 32 Minimum Yield Strength: 85000 pounds per square inch Hole Configuration Style: Hexagon flats Surface Finish: |
| Features Provided: Finished head Thready Qty Per Inch (tpi): 32 Minimum Yield Strength: 85000 pounds per square inch Hole Configuration Style: Hexagon flats Surface Finish: 32.0 microinches threads |
| Features Provided: Finished head Thready Qty Per Inch (tpi): 32 Minimum Yield Strength: 85000 pounds per square inch Hole Configuration Style: Hexagon flats Surface Finish: 32.0 microinches threads Material: |
| Features Provided: Finished head Thready Qty Per Inch (tpi): 32 Minimum Yield Strength: 85000 pounds per square inch Hole Configuration Style: Hexagon flats Surface Finish: 32.0 microinches threads Material: Iron alloy 660 |
| Features Provided: Finished head Thready Qty Per Inch (tpi): 32 Minimum Yield Strength: 85000 pounds per square inch Hole Configuration Style: Hexagon flats Surface Finish: 32.0 microinches threads Material: Iron alloy 660 Material Specification: |
| Features Provided: Finished head Thready Qty Per Inch (tpi): 32 Minimum Yield Strength: 85000 pounds per square inch Hole Configuration Style: Hexagon flats Surface Finish: 32.0 microinches threads Material: Iron alloy 660 Material Specification: Ams 5731 assn standard single material response |
| Features Provided: Finished head Thready Qty Per Inch (tpi): 32 Minimum Yield Strength: 85000 pounds per square inch Hole Configuration Style: Hexagon flats Surface Finish: 32.0 microinches threads Material: Iron alloy 660 Material Specification: Ams 5731 assn standard single material response Thread Series Designator: |
| Features Provided: Finished head Thready Qty Per Inch (tpi): 32 Minimum Yield Strength: 85000 pounds per square inch Hole Configuration Style: Hexagon flats Surface Finish: 32.0 microinches threads Material: Iron alloy 660 Material Specification: Ams 5731 assn standard single material response Thread Series Designator: Unjf |

NSN 5306-00-080-9395

Machine Bolt - Page 2 of 2



| | • • | | | | |
|----|-----|-------------|----|-----|------|
| In | 18 | <i>(</i>)+ | МА | 261 | ıre: |
| | | | | | |

--

Demilitarization:

No

Fiig:

A003b0