

View Online at <https://aerobasegroup.com/nsn/5306-00-082-6647>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 1.475 inches and 1.525 inches

**Fastener Length:**

Between 3.860 inches and 3.890 inches

**Head Diameter:**

Between 1.865 inches and 1.875 inches

**Head Height:**

1.125 inches

**Internal Drive Style:**

Hexagon

**Thread Diameter:**

1.125 inches

**Width Across Flats:**

Between 0.751 inches and 0.755 inches

**Thready Qty Per Inch (tpi):**

12

**Min. Tensile Strength (psi):**

160000 pounds per square inch

**Hardness Rating:**

34.0 rockwell c and 40.0 rockwell c

**Material:**

Steel comp 4140 or steel comp e4340 or steel comp 6150 or steel comp 8735 or steel comp 8740

**Material Specification:**

Mil-s-5626 military specification 1st material response or mil-s-5000 military specification 2nd material response or mil-s-8503 military specification 3rd material response or mil-s-6098 military specification 4th material response or mil-s-6049 military specification 5th material response

**Surface Treatment:**

Cadmium and chromate

**Surface Treatment Specification:**

Qq-p-416, type 2 cl 2 federal specification single treatment response

**Thread Series Designator:**

Unf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0

**Mil-std (military Standard):**

Mil-s-5626 spec.