NSN 5306-00-083-7071

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-00-083-7071

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.298 inches and 0.348 inches
Fastener Length:
Between 3.058 inches and 3.088 inches
Head Style:
Dished hexagon
Head Height:
Between 0.110 inches and 0.125 inches
Width Between Flats:
Between 0.367 inches and 0.376 inches
Grip Diameter:
Between 0.1890 inches and 0.1895 inches
Thread Diameter:
0.190 inches
Grip Length:
Between 2.740 inches and 2.760 inches
Thready Qty Per Inch (tpi):
32
Min. Tensile Strength (psi):
min. Tensile Strength (psi).
160000 pounds per square inch
160000 pounds per square inch
160000 pounds per square inch Surface Finish:
160000 pounds per square inch Surface Finish: 32.0 microinches threads
160000 pounds per square inch Surface Finish: 32.0 microinches threads Material:
160000 pounds per square inch Surface Finish: 32.0 microinches threads Material: Iron alloy 660
160000 pounds per square inch Surface Finish: 32.0 microinches threads Material: Iron alloy 660 Material Specification:
160000 pounds per square inch Surface Finish: 32.0 microinches threads Material: Iron alloy 660 Material Specification: Ams 5731 assn standard single material response or ams 5737 assn standard single material response
160000 pounds per square inch Surface Finish: 32.0 microinches threads Material: Iron alloy 660 Material Specification: Ams 5731 assn standard single material response or ams 5737 assn standard single material response Surface Treatment:
160000 pounds per square inch Surface Finish: 32.0 microinches threads Material: Iron alloy 660 Material Specification: Ams 5731 assn standard single material response or ams 5737 assn standard single material response Surface Treatment: Passivate
160000 pounds per square inch Surface Finish: 32.0 microinches threads Material: Iron alloy 660 Material Specification: Ams 5731 assn standard single material response or ams 5737 assn standard single material response Surface Treatment: Passivate Surface Treatment Specification:
160000 pounds per square inch Surface Finish: 32.0 microinches threads Material: Iron alloy 660 Material Specification: Ams 5731 assn standard single material response or ams 5737 assn standard single material response Surface Treatment: Passivate Surface Treatment Specification: Qq-p-35 federal specification single treatment response
160000 pounds per square inch Surface Finish: 32.0 microinches threads Material: Iron alloy 660 Material Specification: Ams 5731 assn standard single material response or ams 5737 assn standard single material response Surface Treatment: Passivate Surface Treatment Specification: Qq-p-35 federal specification single treatment response Thread Series Designator:
160000 pounds per square inch Surface Finish: 32.0 microinches threads Material: Iron alloy 660 Material Specification: Ams 5731 assn standard single material response or ams 5737 assn standard single material response Surface Treatment: Passivate Surface Treatment Specification: Qq-p-35 federal specification single treatment response Thread Series Designator: Unjf
160000 pounds per square inch Surface Finish: 32.0 microinches threads Material: Iron alloy 660 Material Specification: Ams 5731 assn standard single material response or ams 5737 assn standard single material response Surface Treatment: Passivate Surface Treatment Specification: Qq-p-35 federal specification single treatment response Thread Series Designator: Unjf Specification Data:
160000 pounds per square inch Surface Finish: 32.0 microinches threads Material: Iron alloy 660 Material Specification: Ams 5731 assn standard single material response or ams 5737 assn standard single material response Surface Treatment: Passivate Surface Treatment Specification: Qq-p-35 federal specification single treatment response Thread Series Designator: Unjf Specification Data: 80205-nas6303 professional/industrial association standard

--

NSN 5306-00-083-7071

Shear Bolt - Page 2 of 2



_		••	• •				
וו	em	ш	112	rız	211	n	٠.

No

Fiig:

A003b0