

NSN 5306-00-084-1154 Machine Bolt - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5306-00-084-1154 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.927 inches and 0.967 inches **Fastener Length:** Between 1.052 inches and 1.072 inches **Head Style:** Hexagon **Head Height:** Between 0.271 inches and 0.291 inches Width Between Flats: Between 0.741 inches and 0.752 inches **Hole Diameter:** 0.070 inches **Thread Diameter:** 0.500 inches **Grip Length:** Between 0.105 inches and 0.125 inches **Hole Quantity:** 1 **Hole Type:** Drilled **Features Provided:** Finished head Thready Qty Per Inch (tpi): 20 Min. Tensile Strength (psi): 125000 pounds per square inch

Hardness Rating:

26.0 rockwell c and 32.0 rockwell c

**Hole Configuration Style:** 

Hexagon flats

**Surface Finish:** 

32.0 microinches threads

Material:

Steel comp 8740

**Material Specification:** 

Ams 6322 assn standard single material response

**Surface Treatment:** 

Cadmium

## NSN 5306-00-084-1154

Machine Bolt - Page 2 of 2



Surface	<b>Treatment</b>	Specif	ication:
Juliace	HEALINGIL	Opecii	ıcalıcı.

Ams 2400 assn standard single treatment response

**Thread Series Designator:** 

Unjf

Shelf Life:

N/a

**Unit Of Measure:** 

\_\_

Demilitarization:

No

Fiig:

A003b0