

View Online at <https://aerobasegroup.com/nsn/5306-00-087-6499>

Thread Direction:

Right-hand

Thread Length:

Between 0.330 inches and 0.410 inches

Fastener Length:

Between 0.990 inches and 1.010 inches

Head Style:

Double hexagon w/hole

Head Height:

Between 0.320 inches and 0.340 inches

Width Between Flats:

Between 0.304 inches and 0.313 inches

Extended Washer Diameter:

Between 0.428 inches and 0.448 inches

Extended Washer Thickness:

Between 0.060 inches and 0.070 inches

Hole Diameter:

Between 0.060 inches and 0.080 inches

First Diameter From Head:

Between 0.264 inches and 0.266 inches

Second Diameter From Head:

Between 0.194 inches and 0.198 inches

Distance From Largest Bearing Surface Of Head To End Of First Diameter:

Between 0.370 inches and 0.390 inches

Distance From Largest Bearing Surface Of Head To End Of Second Diameter:

Between 0.600 inches and 0.660 inches

Thread Diameter:

0.250 inches

Hole Quantity:

4

Hole Type:

Drilled

Nonstandard Thread Pitch Diameter:

+0.2213 to 0.2238 inches

Thready Qty Per Inch (tpi):

28

Hole Configuration Style:

Double hexagon longitudinal hole

Externally Relieved Body Diameter Quantity:

2

Special Features:

Minor diameter of thd 0.203 in. Max

Material:

Iron alloy 660

Material Specification:

Ams 5732 assn standard single material response

Thread Series Designator:

Uns

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0