NSN 5306-00-088-2150

Externally Relieved Body Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-00-088-2150 **Thread Class:** За **Thread Length:** Between 0.970 inches and 1.030 inches **Fastener Length:** Between 9.678 inches and 9.708 inches **Head Style:** Double hexagon extended washer **Head Height:** Between 0.547 inches and 0.567 inches Width Between Flats: Between 0.616 inches and 0.627 inches **Extended Washer Diameter:** Between 0.928 inches and 0.938 inches **Extended Washer Thickness:** Between 0.123 inches and 0.143 inches First Diameter From Head: Between 0.559 inches and 0.560 inches **Second Diameter From Head:** Between 0.518 inches and 0.520 inches **Third Diameter From Head:** Between 0.559 inches and 0.560 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 3.242 inches and 3.282 inches Distance From Largest Bearing Surface Of Head To End Of Second Diameter: Between 7.840 inches and 7.880 inches Distance From Largest Bearing Surface Of Head To End Of Third Diameter: Between 8.678 inches and 8.708 inches Material: Steel comp h11 **Material Specification:** Ams6485 assn standard single material response **Surface Treatment:** Cadmium **Surface Treatment Specification:** Nas 672 assn standard single treatment response Shelf Life: N/a **Unit Of Measure:**

Demilitarization:

No

NSN 5306-00-088-2150

Externally Relieved Body Bolt - Page 2 of 2



Fiig:

A003b0