

View Online at <https://aerobasegroup.com/nsn/5306-00-089-9814>

Thread Class:

2a

Thread Direction:

Right-hand

Thread Length:

0.625 inches

Eye Inside Diameter:

0.750 inches

Shank Length:

1.094 inches

Eye Stock Thickness:

0.219 inches

Overall Length:

3.062 inches

Thread Diameter:

0.250 inches

Thready Qty Per Inch (tpi):

28

Distance From Center Of Eye To Shank End:

4.437 inches

Eye Outside Width:

0.500 inches

Material:

Steel comp 1015 or steel comp 1016 or steel comp 1017 or steel comp 1018 or steel comp 1019 or steel comp 1020 or steel comp 1021 or steel comp 1022 or steel comp 1022 or steel comp 1023 or steel comp 1524 or steel comp 1025 or steel comp 1026 or steel comp 1527 or steel comp 1029 or steel comp 1030 or steel comp 1031 or steel comp 1033 or steel comp 1034 or steel comp 1035

Material Specification:

Mil-s-13048 military specification 1st material response or mil-s-13048 federal specification 2nd material response or mil-s-13048 federal specification 3rd material response or mil-s-13048 military specification 4th material response or mil-s-13048 military specification 5th material response or mil-s-13048 military specification all material responses or mil-s-13048 military specification 6th material response or mil-s-13048 military specification 7th material response or mil-s-13048 military specification 8th material response or mil-s-13048 military specification 9th material response or mil-s-13048 military specification 11th material response or mil-s-13048 military specification 12th material response or mil-s-13048 military specification 13th material response or mil-s-13048 military specification 14th material response or mil-s-13048 military specification 15th material response or mil-s-13048 military specification 16th material response or mil-s-13048 military specification 17th material response or mil-s-13048 military specification 18th material response or mil-s-13048 military specification 19th material response or mil-i-11466 gr d4512 military specification 20th material response or mil-i-11466 gr d4018 military specification 21st material response

Surface Treatment:

Cadmium and chromate or enamel

Surface Treatment Specification:

Tt-e-529 federal specification 2nd treatment response threads or tt-e-485 federal specification 2nd treatment response threads

Style Designator:

Round, closed

Thread Series Designator:

Unf

Mil-std (military Standard):

Mil-s-13048 spec.