NSN 5306-00-089-9823

Externally Relieved Body Bolt - Page 1 of 2



| View Online at https://aerobasegroup.com/nsn/5306-00-089-9823 |
|---|
| Thread Class: |
| 3a |
| Thread Direction: |
| Right-hand |
| Thread Length: |
| Between 0.327 inches and 0.367 inches |
| Fastener Length: |
| Between 0.427 inches and 0.447 inches |
| Head Style: |
| Crowned hexagon |
| Head Height: |
| Between 0.621 inches and 0.631 inches |
| Width Between Flats: |
| 0.562 inches |
| First Diameter From Head: |
| Between 0.302 inches and 0.322 inches |
| Distance From Largest Bearing Surface Of Head To End Of First Diameter: |
| Between 0.080 inches and 0.100 inches |
| Thread Diameter: |
| 0.375 inches |
| Thready Qty Per Inch (tpi): |
| 24 |
| Min. Tensile Strength (psi): |
| 125000 pounds per square inch |
| Externally Relieved Body Diameter Quantity: |
| 1 |
| Material: |
| Steel comp e4340 |
| Material Specification: |
| Mil-s-5000, c4 military specification single material response |
| Surface Treatment: |
| Cadmium and chromate |
| Surface Treatment Specification: |
| Qq-o-416, cl 2 federal specification all treatment responses |
| Thread Series Designator: |
| Unf |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |

No

NSN 5306-00-089-9823

Externally Relieved Body Bolt - Page 2 of 2



Fiig:

A003b0

Mil-std (military Standard):

Mil-s-5000 spec.