

View Online at <https://aerobasegroup.com/nsn/5306-00-090-1588>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.450 inches and 0.530 inches

**Fastener Length:**

Between 4.950 inches and 4.970 inches

**Head Style:**

Hexagon

**Head Height:**

Between 0.450 inches and 0.470 inches

**Width Between Flats:**

Between 0.431 inches and 0.440 inches

**Shank Unthreaded Hole Diameter:**

0.065 inches first hole and 0.072 inches first hole

**Thread Diameter:**

0.250 inches

**Grip Length:**

Between 4.440 inches and 4.500 inches

**Features Provided:**

Finished head

**Thready Qty Per Inch (tpi):**

28

**Hardness Rating:**

26.0 rockwell c and 32.0 rockwell c

**Distance From Head Largest Bearing Surface To Shank Hole Center:**

4.845 inches first hole and 4.865 inches first hole

**Material:**

Steel comp 8740

**Material Specification:**

Ams 6322 assn standard single material response

**Surface Treatment:**

Cadmium

**Thread Series Designator:**

Unf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A003b0