

View Online at <https://aerobasegroup.com/nsn/5306-00-094-1900>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

0.406 inches

**Fastener Length:**

2.812 inches

**Head Style:**

Dee

**Head Diameter:**

0.938 inches

**Head Height:**

0.125 inches

**Distance From Centerline To Flat:**

0.375 inches

**Shank Unthreaded Hole Diameter:**

0.141 inches first hole

**First Diameter From Head:**

Between 0.745 inches and 0.747 inches

**Second Diameter From Head:**

Between 0.654 inches and 0.664 inches

**Distance From Largest Bearing Surface Of Head To End Of First Diameter:**

2.281 inches

**Distance From Largest Bearing Surface Of Head To End Of Second Diameter:**

2.406 inches

**Thread Diameter:**

0.750 inches

**Thready Qty Per Inch (tpi):**

16

**Min. Tensile Strength (psi):**

125000 pounds per square inch

**Distance From Head Largest Bearing Surface To Shank Hole Center:**

2.687 inches first hole

**Externally Relieved Body Diameter Quantity:**

2

**Material:**

Steel comp 4130

**Material Specification:**

Sae assn standard single material response

**Surface Treatment:**

Cadmium

**Thread Series Designator:**

Unf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0