NSN 5306-00-094-1900

Externally Relieved Body Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-00-094-1900 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.406 inches **Fastener Length:** 2.812 inches **Head Style:** Dee **Head Diameter:** 0.938 inches **Head Height:** 0.125 inches **Distance From Centerline To Flat:** 0.375 inches **Shank Unthreaded Hole Diameter:** 0.141 inches first hole **First Diameter From Head:** Between 0.745 inches and 0.747 inches **Second Diameter From Head:** Between 0.654 inches and 0.664 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 2.281 inches Distance From Largest Bearing Surface Of Head To End Of Second Diameter: 2.406 inches **Thread Diameter:** 0.750 inches Thready Qty Per Inch (tpi): 16 Min. Tensile Strength (psi): 125000 pounds per square inch Distance From Head Largest Bearing Surface To Shank Hole Center: 2.687 inches first hole **Externally Relieved Body Diameter Quantity:** 2 Material: Steel comp 4130 **Material Specification:**

Sae assn standard single material response

Surface Treatment:

Cadmium

NSN 5306-00-094-1900

Externally Relieved Body Bolt - Page 2 of 2



Thread Series Designator:
Unf
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A003b0