

View Online at <https://aerobasegroup.com/nsn/5306-00-095-2355>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

0.590 inches

**Fastener Length:**

2.250 inches

**Head Style:**

Hexagon

**Head Height:**

0.220 inches

**Width Between Flats:**

0.560 inches

**First Diameter From Head:**

Between 0.372 inches and 0.373 inches

**Second Diameter From Head:**

Between 0.310 inches and 0.315 inches

**Third Diameter From Head:**

Between 0.372 inches and 0.373 inches

**Fourth Diameter From Head:**

Between 0.310 inches and 0.315 inches

**Distance From Largest Bearing Surface Of Head To End Of First Diameter:**

0.019 inches

**Distance From Largest Bearing Surface Of Head To End Of Second Diameter:**

0.066 inches

**Distance From Largest Bearing Surface Of Head To End Of Third Diameter:**

1.040 inches

**Distance From Largest Bearing Surface Of Head To End Of Fourth Diameter:**

1.660 inches

**Thread Diameter:**

0.375 inches

**Thready Qty Per Inch (tpi):**

24

**Hardness Rating:**

30.0 rockwell c and 35.0 rockwell c

**Externally Relieved Body Diameter Quantity:**

4

**Special Features:**

2 holes 90.0 degrees apart

**Material:**

Steel comp 8740

**Thread Series Designator:**

Unf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0