NSN 5306-00-097-4826

Close Tolerance Bolt - Page 1 of 1

AeroBase Group

View Online at https://aerobasegroup.com/nsn/5306-00-097-4826

Thread Class:
3a
Thread Direction:
Right-hand
Fastener Length:
Between 1.626 inches and 1.656 inches
Head Style:
Hexagon
Head Height:
Between 0.188 inches and 0.203 inches
Width Between Flats:
Between 0.553 inches and 0.564 inches
Grip Diameter:
Between 0.3740 inches and 0.3750 inches
Shank Unthreaded Hole Diameter:
0.106 inches first hole and 1.116 inches first hole
Thread Diameter:
0.375 inches
Grip Length:
Between 1.240 inches and 1.260 inches
Thready Qty Per Inch (tpi):
24
Distance From Head Largest Bearing Surface To Shank Hole Center:
Distance From Head Largest Bearing Surface To Shank Hole Center: 1.518 inches first hole and 1.528 inches first hole
1.518 inches first hole and 1.528 inches first hole
1.518 inches first hole and 1.528 inches first hole Surface Finish:
1.518 inches first hole and 1.528 inches first holeSurface Finish:63.0 microinches grip
 1.518 inches first hole and 1.528 inches first hole Surface Finish: 63.0 microinches grip Material:
 1.518 inches first hole and 1.528 inches first hole Surface Finish: 63.0 microinches grip Material: Titanium alloy uns r54520
 1.518 inches first hole and 1.528 inches first hole Surface Finish: 63.0 microinches grip Material: Titanium alloy uns r54520 Material Specification:
 1.518 inches first hole and 1.528 inches first hole Surface Finish: 63.0 microinches grip Material: Titanium alloy uns r54520 Material Specification: Nas621 com+6al-4v assn standard single material response
 1.518 inches first hole and 1.528 inches first hole Surface Finish: 63.0 microinches grip Material: Titanium alloy uns r54520 Material Specification: Nas621 com+6al-4v assn standard single material response Thread Series Designator:
 1.518 inches first hole and 1.528 inches first hole Surface Finish: 63.0 microinches grip Material: Titanium alloy uns r54520 Material Specification: Nas621 com+6al-4v assn standard single material response Thread Series Designator: Unf
 1.518 inches first hole and 1.528 inches first hole Surface Finish: 63.0 microinches grip Material: Titanium alloy uns r54520 Material Specification: Nas621 com+6al-4v assn standard single material response Thread Series Designator: Unf Specification Data:
 1.518 inches first hole and 1.528 inches first hole Surface Finish: 63.0 microinches grip Material: Titanium alloy uns r54520 Material Specification: Nas621 com+6al-4v assn standard single material response Thread Series Designator: Unf Specification Data: 80205-nas656 professional/industrial association standard
 1.518 inches first hole and 1.528 inches first hole Surface Finish: 63.0 microinches grip Material: Titanium alloy uns r54520 Material Specification: Nas621 com+6al-4v assn standard single material response Thread Series Designator: Unf Specification Data: 80205-nas656 professional/industrial association standard Shelf Life:
 1.518 inches first hole and 1.528 inches first hole Surface Finish: 63.0 microinches grip Material: Titanium alloy uns r54520 Material Specification: Nas621 com+6al-4v assn standard single material response Thread Series Designator: Unf Specification Data: 80205-nas656 professional/industrial association standard Shelf Life: N/a
 1.518 inches first hole and 1.528 inches first hole Surface Finish: 63.0 microinches grip Material: Titanium alloy uns r54520 Material Specification: Nas621 com+6al-4v assn standard single material response Thread Series Designator: Unf Specification Data: 80205-nas656 professional/industrial association standard Shelf Life: N/a Unit Of Measure:
1.518 inches first hole and 1.528 inches first hole Surface Finish: 63.0 microinches grip Material: Titanium alloy uns r54520 Material Specification: Nas621 com+6al-4v assn standard single material response Thread Series Designator: Unf Specification Data: 80205-nas656 professional/industrial association standard Shelf Life: N/a Unit Of Measure:
1.518 inches first hole and 1.528 inches first hole Surface Finish: 63.0 microinches grip Material: Titanium alloy uns r54520 Material Specification: Nas621 com+6al-4v assn standard single material response Thread Series Designator: Unf Specification Data: 80205-nas656 professional/industrial association standard Shelf Life: N/a Unit Of Measure:
1.518 inches first hole and 1.528 inches first hole Surface Finish: 63.0 microinches grip Material: Titanium alloy uns r54520 Material Specification: Nas621 com+6al-4v assn standard single material response Thread Series Designator: Unf Specification Data: 80205-nas656 professional/industrial association standard Shelf Life: N/a Unit Of Measure: Demilitarization: No