Machine Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-00-097-7360

Thre	ead Class:
3a	
Thre	ead Direction:
Righ	it-hand
Thre	ead Length:
1.06	2 inches
Fast	ener Length:
1.25	0 inches
Head	d Style:
Doul	ble hexagon extended washer
Head	d Height:
0.42	2 inches
Widt	th Between Flats:
Betw	veen 0.430 inches and 0.439 inches
Exte	ended Washer Diameter:
Betw	veen 0.639 inches and 0.649 inches
Exte	ended Washer Thickness:
0.09	5 inches
Thre	ead Diameter:
0.37	5 inches
Grip	Length:
0.18	8 inches
Feat	ures Provided:
Finis	shed head
Thre	eady Qty Per Inch (tpi):
24	
Harc	dness Rating:
36.0	rockwell c and 40.0 rockwell c
Proc	duct Name:
Navy	y special project
Spe	cial Features:
4 gro	boves across head, 90 degrees apart, 0.062 in. Nom, w, 0.062 in. Nom, deep
Mate	erial:
Stee	1
Surf	ace Treatment:
Cad	mium
Surf	ace Treatment Specification:
Qq-p	p-416, type 2, class 3 federal specification single treatment response
Test	Data Document:
8134	19-mili6868 specification (includes engineering type bulletins, brochures, etc.,

81349-mili6868 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

## Thread Series Designator:

## NSN 5306-00-097-7360

Machine Bolt - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A003b0

