NSN 5306-00-102-3088

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/psn/5306-00-102-3088

View Online at https://aerobasegroup.com/nsn/5306-00-102-3088
Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.557 inches and 0.607 inches
Fastener Length:
Between 1.755 inches and 1.785 inches
Head Style:
Double hexagon w/hole
Head Height:
0.319 inches
Width Between Flats:
Between 0.367 inches and 0.376 inches
Extended Washer Diameter:
Between 0.575 inches and 0.585 inches
Extended Washer Thickness:
0.050 inches
Grip Diameter:
Between 0.3110 inches and 0.3120 inches
Thread Diameter:
0.312 inches
Grip Length:
Between 1.178 inches and 1.198 inches
Thready Qty Per Inch (tpi):
24
Min. Tensile Strength (psi):
220000 pounds per square inch
Hardness Rating:
46.0 rockwell c and 50.0 rockwell c
Material:
Steel comp h11
Material Specification:
Ams 6485 assn standard single material response or ams 6487 assn standard single material response
Surface Treatment:
Cadmium
Surface Treatment Specification:
Nas 672 assn standard single treatment response
Thread Series Designator:
Unjf
Specification Data:

50392-ewb22 manufacturers standard

NSN 5306-00-102-3088

Shear Bolt - Page 2 of 2



Shelf Life:	She	lf	Life:
-------------	-----	----	-------

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0