NSN 5306-00-104-1680

Externally Relieved Body Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-00-104-1680 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.290 inches and 0.330 inches **Fastener Length:** Between 0.800 inches and 0.820 inches **Head Style:** Hexagon **Head Height:** Between 0.240 inches and 0.260 inches Width Between Flats: Between 0.432 inches and 0.442 inches **First Diameter From Head:** Between 0.245 inches and 0.255 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.490 inches and 0.510 inches **Thread Diameter:** 0.312 inches Thready Qty Per Inch (tpi): 24 **Externally Relieved Body Diameter Quantity: Special Features:** Hole 0.221 in. Diameter by 0.500 in. Lg drilled through head along longitudinal axis Material: Steel comp 303 **Material Specification:** Qq-s-764 federal specification single material response **Surface Treatment: Passivate Surface Treatment Specification:** Mil-f-14072, finish e300 military specification single treatment response **Thread Series Designator:** Unf Shelf Life: N/a **Unit Of Measure:**

Demilitarization:

No

NSN 5306-00-104-1680

Externally Relieved Body Bolt - Page 2 of 2



Fiig:

A003b0

Mil-std (military Standard):

Mil-f-14072 spec.