

View Online at <https://aerobasegroup.com/nsn/5306-00-104-2949>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.368 inches and 0.518 inches

Fastener Length:

Between 3.150 inches and 3.180 inches

Head Style:

Double hexagon

Head Height:

0.257 inches

Width Between Flats:

Between 0.678 inches and 0.689 inches

Grip Diameter:

Between 0.4355 inches and 0.4365 inches

Shank Unthreaded Hole Diameter:

0.106 inches first hole and 0.116 inches first hole

Thread Diameter:

0.438 inches

Grip Length:

Between 2.662 inches and 2.682 inches

Thread Qty Per Inch (tpi):

20

Min. Tensile Strength (psi):

260000 pounds per square inch

Hardness Rating:

51.0 rockwell c and 54.0 rockwell c

Distance From Head Largest Bearing Surface To Shank Hole Center:

3.011 inches first hole

Material:

Steel comp h11

Material Specification:

Ams 6487 assn standard single material response

Surface Treatment:

Cadmium and chromate

Surface Treatment Specification:

Ams 2416 assn standard all treatment responses

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0