

View Online at <https://aerobasegroup.com/nsn/5306-00-105-4531>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.312 inches and 0.337 inches

**Fastener Length:**

Between 0.750 inches and 0.765 inches

**Head Style:**

Crowned hexagon

**Head Height:**

Between 0.095 inches and 0.110 inches

**Width Between Flats:**

Between 0.367 inches and 0.376 inches

**Shank Unthreaded Hole Diameter:**

0.076 inches and 0.086 inches first hole

**Thread Diameter:**

0.190 inches

**Grip Length:**

Between 0.428 inches and 0.438 inches

**Features Provided:**

Finished head

**Thready Qty Per Inch (tpi):**

32

**Min. Tensile Strength (psi):**

130000 pounds per square inch

**Hardness Rating:**

248.0 brinell standard and 341.0 brinell standard

**Minimum Yield Strength:**

85000 pounds per square inch

**Distance From Head Largest Bearing Surface To Shank Hole Center:**

0.675 inches first hole

**Surface Finish:**

32.0 microinches grip

**Special Features:**

Spring loaded ball in shank 0.244 in. From head

**Material:**

Stainless steel

**Material Specification:**

Ams 5731 assn standard single material response or ams 5736 assn standard single material response or qq-s-763 federal specification single material response or 54-71a, fscm 73342 mfr ref single material response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0