NSN 5306-00-106-6534

Machine Bolt - Page 1 of 2

Thread Class:

Right-hand

Thread Direction:

За



View Online at https://aerobasegroup.com/nsn/5306-00-106-6534

Thread Length:
Between 0.303 inches and 0.385 inches
Fastener Length:
Between 0.365 inches and 0.385 inches
Head Style:
Double hexagon w/hole
Head Height:
Between 0.250 inches and 0.270 inches
Width Between Flats:
Between 0.243 inches and 0.251 inches
Extended Washer Diameter:
Between 0.365 inches and 0.385 inches
Extended Washer Thickness:
Between 0.040 inches and 0.050 inches
Hole Diameter:
0.047 inches
Thread Diameter:
0.190 inches
Hole Quantity:
4
Hole Type:
Drilled
Features Provided:
Finished head
Thready Qty Per Inch (tpi):
rineady with Let mon (thi).
32
32
32 Min. Tensile Strength (psi):
32 Min. Tensile Strength (psi): 125000 pounds per square inch
32 Min. Tensile Strength (psi): 125000 pounds per square inch Hardness Rating:
Min. Tensile Strength (psi): 125000 pounds per square inch Hardness Rating: 26.0 rockwell c and 32.0 rockwell c
Min. Tensile Strength (psi): 125000 pounds per square inch Hardness Rating: 26.0 rockwell c and 32.0 rockwell c Hole Configuration Style:
Min. Tensile Strength (psi): 125000 pounds per square inch Hardness Rating: 26.0 rockwell c and 32.0 rockwell c Hole Configuration Style: Round
Min. Tensile Strength (psi): 125000 pounds per square inch Hardness Rating: 26.0 rockwell c and 32.0 rockwell c Hole Configuration Style: Round Surface Finish:
Min. Tensile Strength (psi): 125000 pounds per square inch Hardness Rating: 26.0 rockwell c and 32.0 rockwell c Hole Configuration Style: Round Surface Finish: 63.0 microinches bearing surface of head
Min. Tensile Strength (psi): 125000 pounds per square inch Hardness Rating: 26.0 rockwell c and 32.0 rockwell c Hole Configuration Style: Round Surface Finish: 63.0 microinches bearing surface of head Material:
Min. Tensile Strength (psi): 125000 pounds per square inch Hardness Rating: 26.0 rockwell c and 32.0 rockwell c Hole Configuration Style: Round Surface Finish: 63.0 microinches bearing surface of head Material: Steel comp 8740
Min. Tensile Strength (psi): 125000 pounds per square inch Hardness Rating: 26.0 rockwell c and 32.0 rockwell c Hole Configuration Style: Round Surface Finish: 63.0 microinches bearing surface of head Material: Steel comp 8740 Material Specification:

NSN 5306-00-106-6534 Machine Bolt - Page 2 of 2

Fiig: A003b0



Surface Treatment:
Oxide film
Surface Treatment Specification:
Ams 2485 assn standard single treatment response
Thread Series Designator:
Unjf
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No