NSN 5306-00-107-2225

Shoulder Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-00-107-2225 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.555 inches and 0.605 inches **Fastener Length:** Between 1.835 inches and 1.865 inches **Head Style:** Hexagon **Head Height:** Between 0.209 inches and 0.229 inches Width Between Flats: Between 0.553 inches and 0.564 inches **Shoulder Diameter:** 0.3740 inches first shoulder and 0.3745 inches first shoulder **Shoulder Length:** 1.260 inches first shoulder and 1.280 inches first shoulder **Thread Diameter:** 0.312 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 130000 pounds per square inch Hardness Rating: 248.0 brinell standard and 341.0 brinell standard Minimum Yield Strength: 85000 pounds per square inch **Shoulder Shape:** Round first shoulder Material: Iron alloy 660 **Material Specification:** Ams 5731 assn standard single material response **Thread Series Designator:** Unjf Shelf Life: N/a **Unit Of Measure:**

Demilitarization:

No

NSN 5306-00-107-2225 Shoulder Bolt - Page 2 of 2



Fiig:

A003b0