

View Online at <https://aerobasegroup.com/nsn/5306-00-108-9838>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.291 inches and 0.341 inches

Fastener Length:

Between 5.551 inches and 5.581 inches

Head Style:

Dished hexagon

Head Height:

Between 0.125 inches and 0.140 inches

Width Between Flats:

Between 0.430 inches and 0.439 inches

Grip Diameter:

Between 0.2485 inches and 0.2495 inches

Shank Unthreaded Hole Diameter:

0.076 inches first hole and 0.086 inches first hole

Thread Diameter:

0.250 inches

Grip Length:

Between 5.240 inches and 5.260 inches

Thread Qty Per Inch (tpi):

28

Min. Tensile Strength (psi):

160000 pounds per square inch

Hardness Rating:

36.0 rockwell c and 40.0 rockwell c

Distance From Head Largest Bearing Surface To Shank Hole Center:

5.425 inches first hole and 5.475 inches first hole

Material:

Steel comp 4140 or steel comp e4340 or steel comp 6150 or steel comp 8735 or steel comp 8740

Surface Treatment:

Cadmium and chromate

Surface Treatment Specification:

Qq-p-416 type 2 class 3 federal specification single treatment response

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A003b0