NSN 5306-00-110-2918

Externally Relieved Body Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-00-110-2918 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.200 inches and 0.271 inches **Fastener Length:** Between 0.665 inches and 0.690 inches **Head Style:** Dee chamfer **Head Diameter:** Between 0.500 inches and 0.510 inches **Head Height:** Between 0.140 inches and 0.150 inches **Distance From Centerline To Flat:** Between 0.189 inches and 0.192 inches First Diameter From Head: Between 0.2490 inches and 0.2495 inches **Second Diameter From Head:** Between 0.221 inches and 0.231 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.240 inches and 0.250 inches Distance From Largest Bearing Surface Of Head To End Of Second Diameter: Between 0.354 inches and 0.369 inches **Thread Diameter:** 0.250 inches Thready Qty Per Inch (tpi): **Externally Relieved Body Diameter Quantity:** 2 **Product Name:** Navy special project **Special Features:** 0.040 to 0.050 inch tip, 0.120 to 0.125 in. Dia Material:

Steel comp 8740

Material Specification:

Ams 63223sftt2ahdcda000 assn standard single material response

Surface Treatment:

Cadmium point

Surface Treatment Specification:

Ams 2400 assn standard single treatment response threads

NSN 5306-00-110-2918

Externally Relieved Body Bolt - Page 2 of 2



Thread Series Designator:
Unjf
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A003b0