## NSN 5306-00-110-6315

Machine Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-00-110-6315

| Thread Class:                         |
|---------------------------------------|
| 3a                                    |
| Thread Direction:                     |
| Right-hand                            |
| Thread Length:                        |
| Between 0.570 inches and 0.610 inches |
| Fastener Length:                      |
| Between 1.610 inches and 1.630 inches |
| Head Style:                           |
| Double hexagon w/hole                 |
| Head Height:                          |
| Between 0.310 inches and 0.330 inches |
| Width Between Flats:                  |
| Between 0.304 inches and 0.313 inches |
| Extended Washer Diameter:             |
| Between 0.428 inches and 0.448 inches |
| Extended Washer Thickness:            |
| Between 0.060 inches and 0.070 inches |
| Thread Diameter:                      |
| 0.250 inches                          |
| Grip Length:                          |
| Between 1.020 inches and 1.040 inches |
| Features Provided:                    |
| Finished head                         |
| Thready Qty Per Inch (tpi):           |
| 28                                    |
| Min. Tensile Strength (psi):          |
| 150000 pounds per square inch         |
| Hardness Rating:                      |
| 30.0 rockwell c                       |
| Minimum Yield Strength:               |
| 100000 pounds per square inch         |
| Surface Finish:                       |
| 63.0 microinches grip                 |
| Material:                             |
| Stainless steel                       |
| Thread Series Designator:             |
| Unjf                                  |
| Shelf Life:                           |
| N/a                                   |
| Unit Of Measure:                      |
|                                       |

--

## **NSN 5306-00-110-6315**Machine Bolt - Page 2 of 2



| em |  |  |  |
|----|--|--|--|
|    |  |  |  |
|    |  |  |  |

No

Fiig:

A003b0