

View Online at <https://aerobasegroup.com/nsn/5306-00-113-1431>

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Thread Length:**

0.312 inches

**Fastener Length:**

3.625 inches

**Head Diameter:**

0.375 inches

**Head Height:**

0.250 inches

**First Diameter From Head:**

0.250 inches

**Second Diameter From Head:**

Between 0.211 inches and 0.215 inches

**Third Diameter From Head:**

0.250 inches

**Distance From Largest Bearing Surface Of Head To End Of First Diameter:**

Between 0.742 inches and 0.758 inches

**Distance From Largest Bearing Surface Of Head To End Of Second Diameter:**

Between 0.771 inches and 0.793 inches

**Distance From Largest Bearing Surface Of Head To End Of Third Diameter:**

3.313 inches

**Internal Drive Style:**

Hexagon

**Thread Diameter:**

0.250 inches

**Width Across Flats:**

0.156 inches

**Thready Qty Per Inch (tpi):**

28

**Product Name:**

Navy special project

**Special Features:**

Straight knurl on head

**Material:**

Steel comp 302

**Material Specification:**

Aisi assn standard single material response

**Surface Treatment:**

Passivate

**Surface Treatment Specification:**

580-0025-000 13499 mfr ref single treatment response

**Thread Series Designator:**

Unf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0