

View Online at <https://aerobasegroup.com/nsn/5306-00-113-6240>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.500 inches and 0.579 inches

**Fastener Length:**

Between 0.578 inches and 0.625 inches

**Head Style:**

Hexagon

**Head Height:**

Between 0.172 inches and 0.204 inches

**Width Between Flats:**

Between 0.490 inches and 0.502 inches

**Hole Diameter:**

0.070 inches

**Thread Diameter:**

0.312 inches

**Grip Length:**

Between 0.046 inches and 0.078 inches

**Hole Quantity:**

1

**Hole Type:**

Drilled

**Features Provided:**

Finished head

**Thready Qty Per Inch (tpi):**

24

**Min. Tensile Strength (psi):**

62000 pounds per square inch

**Hole Configuration Style:**

Hexagon flats

**Material:**

Aluminum alloy

**Material Specification:**

Qq-a-200 federal specification single material response or qq-a-225 federal specification single material response or qq-a-430 federal specification single material response

**Surface Treatment:**

Oxide film and anodize

**Surface Treatment Specification:**

Mil-c-5541 military specification 1st treatment response and mil-a-8625 military specification 2nd treatment response

**Thread Series Designator:**

Unf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0

**Mil-std (military Standard):**

Mil-c-5541 spec.