

View Online at <https://aerobasegroup.com/nsn/5306-00-113-7657>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.928 inches and 0.948 inches

**Fastener Length:**

Between 0.928 inches and 0.948 inches

**Head Style:**

Double hexagon extended washer

**Head Height:**

Between 0.520 inches and 0.540 inches

**Width Between Flats:**

Between 0.553 inches and 0.564 inches

**Extended Washer Diameter:**

Between 0.740 inches and 0.760 inches

**Extended Washer Thickness:**

Between 0.125 inches and 0.135 inches

**Hole Diameter:**

0.070 inches

**Thread Diameter:**

0.500 inches

**Hole Quantity:**

4

**Hole Type:**

Drilled

**Features Provided:**

Finished head

**Thready Qty Per Inch (tpi):**

20

**Hardness Rating:**

28.0 rockwell c and 32.0 rockwell c

**Hole Configuration Style:**

Double hexagon flats

**Surface Finish:**

63.0 microinches head

**Material:**

Steel comp 8740

**Material Specification:**

Ams 6322 assn standard single material response

**Surface Treatment:**

Cadmium

**Surface Treatment Specification:**

Ams 2400 assn standard single treatment response

**Thread Series Designator:**

Unf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0